



MAN LIFT

EXPLOSION
PROOF **EX**



1330EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	19 ft	5.75 m
Raised Platform Height	13 ft	3.90 m
Platform Size (inside)	30 in x 50 in	0.76 m x 1.28 m
Platform Capacity	500 lbs	227 kg
Overall Width	30 in	0.76 m
Overall Length	59 in	1.49 m
Stowed Height	79.5 in	2.02 m
Deck Extension	5 ft	0.51 m
Ground Clearance (Raised)	2.4 in	6 cm
Wheelbase	41 in	1.05 m
Inside Turning Radius	14 in	0.35 m
Drive Speed (Stowed)	1.09 mph	3.0 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Gross Weight	3,400 lbs	1,542 kg
Batteries	4 x 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications subject to change

S

SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E


STANDARD EQUIPMENT

- 13 ft Platform Height
- 19 ft Working Height
- 30 x 50 in Platform Size
- 2.4 in Ground Clearance
- 500 lb Platform Capacity
- 5 ft Extendable Deck
- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

O

OPTIONAL

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- 5 ft Powered Extendable Deck
- Dual 4 ft Roll-out or Powered Extendable Decks
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Extension Gate w/ Fall Arrest System
- Scissor Stack Bellow
- EX Rated LED Task Lighting

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com
sales@manliftusa.com