



MAN LIFT

EXPLOSION
PROOF **EX**



1532EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	21 ft	6.4 m
Raised Platform Height	15 ft	4.6 m
Lowered Platform Height	34.5 in	0.9 m
Platform Size (inside)	26 × 64 in	0.66 × 1.6 m
Platform Capacity	600 lbs	272 kg
Overall Width	32 in	0.81 m
Overall Length	89 in	2.26 m
Stowed Height	74 in	1.9 m
Deck Extension	3 ft	0.91 m
Ground Clearance (Stowed)	2.375 in	6 cm
Ground Clearance (Raised)	0.7 in	1.8 cm
Wheelbase	55 in	1.4 m
Inside Turning Radius	Zero	
Outside Turning Radius	66 in	1.68 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Gross Weight	4,060 lbs	1,841 kg
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications subject to change

S

SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E

STANDARD EQUIPMENT

- 15 ft Platform Height
- 21 ft Working Height
- 26 × 64 in Platform Size
- 2.375 in Ground Clearance
- 600 lb Platform Capacity
- 3 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

O

OPTIONAL

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Extension Gate w/ Fall Arrest System
- Scissor Stack Bellow
- EX Rated LED Task Lighting

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com