



MAN LIFT

EXPLOSION
PROOF **EX**



2668EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	32 ft	9.8 m
Raised Platform Height	26 ft	7.9 m
Lowered Platform Height	50 in	1.3 m
Platform Size (inside)	57 × 84 in	1.4 × 2.1 m
Platform Capacity	1200 lbs	544 kg
Overall Width	68 in	1.7 m
Overall Length	118.5 in	3.01 m
Stowed Height	95.5 in	2.4 m
Deck Extension	5 ft	1.5 m
Ground Clearance (Stowed)	7.5 in	19.1 cm
Ground Clearance (Raised)	0.7 in	1.8 cm
Wheelbase	76 in	1.93 m
Inside Turning Radius	76 in	1.93 m
Outside Turning Radius	164 in	4.2 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h
Gross Weight	8,800 lbs	3,991 kg
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications subject to change

S

SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E

STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 57 × 84 in Platform Size
- 7.5 in Ground Clearance
- 1200 lb Platform Capacity
- 5 ft Extendable Deck
- 300 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

O

OPTIONAL

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- 5 ft Powered Extension Deck
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Extension Gate w/ Fall Arrest System
- Scissor Stack Bellow
- EX Rated LED Task Lighting

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com