







3247EX EXPLOSION PROOF SCISSOR LIFT

SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E STANDARD EQUIPMENT

- 32 ft Platform Height
- 38 ft Working Height
- 42 × 84 in Platform Size
- 3.5 in Ground Clearance
- 700 lb Platform Capacity
- 4 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

OPTIONAL

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Extension Gate w/ Fall Arrest System
- Scissor Stack Bellow
- EX Rated LED Task Lighting

SPECIFICATIONS

	Working Height	38 ft	11.6 m
	Raised Platform Height	32 ft	9.8 m
	Lowered Platform Height	48.5 in	1.2 m
	Platform Size (inside)	42 × 84 in	1.1 × 2.1 m
	Platform Capacity	700 lbs	318 kg
	Overall Width	47 in	1.19 m
	Overall Length	108 in	2.75 m
	Stowed Height	88 in	2.2 m
	Deck Extension	4 ft	1.2 m
	Ground Clearance (Stowed)	3.5 in	8.9 cm
	Ground Clearance (Raised)	0.75 in	1.9 cm
	Wheelbase	69 in	1.8 m
	Inside Turning Radius	47.5 in	1.2 m
	Outside Turning Radius	93.5 in	2.4 m
	Drive Speed (Stowed)	1 mph	1.6 km/h
	Drive Speed (Raised)	0.6 mph	1 km/h
	Gross Weight	7,100 lbs	3,220 kg
	Batteries	4 × 6V 250 Amp-hr	
	Charger	20 Amp Automatic SCR	

Specifications subject to change





Manufacturer of Custom Aerial Lifts

manliftusa.com sales@manliftusa.com