



MAN LIFT

EXPLOSION
PROOF **EX**



5392EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

Working Height	59 ft	17.98 m
Raised Platform Height	53 ft	16.15 m
Lowered Platform Height	82 in	2.08 m
Platform Size (inside)	71.65 × 171.7 in	1.82 × 4.36 m
Platform Capacity	1,500 lbs	680 kg
Overall Width	90.6 in	2.30 m
Overall Length	174 in	4.42 m
Stowed Height	126 in	3.19 m
Deck Extension	5 ft	1.52 m
Ground Clearance	10 in	26 cm
Wheelbase	119 in	3.02 m
Inside Turning Radius	128 in	3.25 m
Outside Turning Radius	252 in	6.40 m
Drive Speed (Stowed)	3.5 mph	5.6 km/h
Drive Speed (Raised)	0.6 mph	1 km/h
Gross Weight	20,750 lbs	9,412 kg
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

Specifications subject to change

S

SAFETY

- Explosion Proof
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E

STANDARD EQUIPMENT

- 53 ft Platform Height
- 59 ft Working Height
- 71.65 × 171.7 in Platform Size
- 10 in Ground Clearance
- 1500 lb Platform Capacity
- 5 ft Extendable Deck
- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

O

OPTIONAL

- Padded Aircraft Rails
- Enhanced Padded Aircraft Rails
- 3/8" Airline to Platform
- 5 ft Powered Extendable Deck
- Dual 5 ft Roll-out or Powered
- Extendable Decks
- Remote Mount 600 Amp Charger & Battery
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Extension Gate w/ Fall Arrest System
- Scissor Stack Bellow
- EX Rated LED Task Lighting

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com