







A30JEX EXPLOSION PROOF ARTICULATING BOOM LIFT

SAFETY

E

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 30 ft Platform Height
- 36 ft Working Height
- 30 × 48 in Platform Size
- 4 in Ground Clearance
- 500 lb Platform Capacity
- 20 ft 1 in Horizontal ReachProportional Hydraulic Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm
- 250 Amp Hr Battery

OPTIONAL

- Soft Touch System
- 3/8" or 1/2" Airline to Platform
- Spare Battery Pack
- Open Face Platform
- Fall Arrest System
- EX Rated LED Task Lighting

SPECIFICATIONS

Working Height	36 ft	10.97 m
Platform Height	30 ft	9.14 m
Up and Over Height	13 ft 2 in	4.01 m
Platform Size	30 × 48 in	.76 × 1.22 m
Platform Capacity	500 lbs	227 kg
Overall Width	4 ft	1.22 m
Stowed Length	18 ft 10 in	5.74 m
Stowed Height	6 ft 7 in	2.01 m
Jib Range of Articulation	144° (+84 / -60) vertical	
Articulating Jib	6 ft	1.83 m
Ground Clearance (Axle)	4 in	10 cm
Horizontal Reach	20 ft 1 in	6.12 m
Tailswing	Zero	
Outside Turning Radius	10 ft 2 in	3.1 m
Drive Speed	1 mph	1.6 km/h
Turret Rotation	350°	
Batteries	48v DC	
Platform Rotation	180°	
Gross Weight	15,000 lbs	6,818 kg

Specifications subject to change





Manufacturer of Custom Aerial Lifts

manliftusa.com sales@manliftusa.com