



MAN LIFT



A60Ji

ELECTRICALLY INSULATED BOOM

SPECIFICATIONS

Working Height	66 ft	20 m
Platform Height	60 ft	18 m
Up and Over Height	26 ft 7 in	8.1 m
Platform Size (inside)	24 × 48 in	0.66 m x 1.2 m
Platform Capacity	500 lbs	227 kg
Overall Width	8 ft 2 in	2.49 m
Stowed Length	36 ft 9 in	11.24 m
Stowed Height	8 ft 4 in	2.54 m
Jib Length	72 in	1.83 m
Horizontal Reach	34 ft 3 in	10.45 m
Outside Turning Radius	17 ft 7 in	5.36 m
Drive Speed	4.25 mph	6.84 kmh
Horizontal Platform Rotation		180°
Vertical Jib Rotation		130° (+70 / -60)
Ground Clearance (axle)	11.7 in	0.29 m
Turret Rotation		360°
Engine Type		Diesel
Platform Rotation		180°
Gradeability		2WD - 30% / 4WD - 45%
Swing		360°
Drive Type		2WD or 4WD (Optional)
Est. Gross Gross Weight	22,200 lbs	10,070 kg

Specifications subject to change

S

SAFETY

- 46kV Electrically Insulated
- ANSI 92.2 46kV Category C Rating
- 3rd Party Certified
- Fiberglass Boom Section
- 1 or 2 Person Fiberglass Bucket w/ Liner
- Fiber Optic Module Controls
- Non-Conductive Hydraulic Hoses
- Fall Protection

E

STANDARD EQUIPMENT

- 60 ft Platform Height
- 66 ft Working Height
- 26 in x 48 in Platform Size
- 11.7 in Ground Clearance
- 500 lb Platform Capacity
- Diesel Engine
- 12V DC Battery
- Factory Controls Retained For Operator Ease of Use

O

OPTIONAL

- Customer and Market Driven Design
- Wireless Bluetooth Platform Controls
- 6 ft Articulating Jib
- Optional 2WD or 4WD

MADE IN THE
USA



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com