



MAN LIFT A73TDi



A73TDi ELECTRICALLY INSULATED TRACK- DRIVE LIFT

SPECIFICATIONS

Working Height	79 ft	24.1 m
Platform Height	73 ft	22.3 m
Outreach	35 ft	10.7 m
Rotation	360° Non-continuous	
Platform Size	24 x 24 x 42 in	.6 x .6 x 1.1 m
Platform Capacity	300 lbs	136 kg
Controls	Radio Remote	
Stowed Height	78 in	2.0 m
Stowed Length	27 ft 5 in	8.4 m
Width	34.5 in	0.88 m
Power Source	Diesel	
Speed	1.5 mph	2.4 kph
Gross Weight	8,200 lbs	3,583 kg

Specifications subject to change

S SAFETY

- 46kV electrically insulated
- ANSI 92.2 46kV category "C" rating
- 6 ft articulating fiberglass boom
- Fiberglass bucket with liner
- Non-conductive hydraulic hoses
- Fall Protection
- Pedestrian barrier

P PRODUCTIVE

- Access to narrow areas that can't be reached with a bucket truck
- Extremely Compact: 34.5 in width; 78 in stowed height
- 79 ft working height; 35 ft outreach
- High speed drive mode

I INNOVATIVE

- Customer and market driven design in response to real industry challenges
- High strength steel construction for increased stability
- Tool circuit
- Radio remote control
- Front facing bucket controls
- Digital diagnostic displays for advanced troubleshooting

C STANDARDS COMPLIANCE

- ANSI 92.2 46kV category "C" rating

E ELECTRICALLY INSULATED

- 6 ft fiberglass boom
- Fiberglass bucket with liner
- Non-conductive hydraulic hoses



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com