



MAN LIFT

EXPLOSION
PROOF **EX**

AE60JEX EXPLOSION PROOF ARTICULATING BOOM LIFT



SPECIFICATIONS

Working Height	66 ft	20.11 m
Platform Height	60 ft	18.47 m
Up and Over Height	26 ft 7 in	8.1 m
Platform Size (inside)	36 × 96 in	.91 × 2.44 m
Platform Capacity	500 lbs	227 kg
Overall Width	8 ft	2.44 m
Stowed Length	26 ft 5 in	6.53 m
Stowed Height	8 ft 4 in	2.24 m
Jib Range of Articulation	144° (+78, -70) vertical	
Articulating Jib	6 ft	1.83 m
Ground Clearance (Axle)	12 in	30 cm
Tailswing	4 ft	1.22 m
Outside Turning Radius	11 ft 8 in	3.56 m
Drive Speed	1 mph	1.6 km/h
Turret Rotation		300°
Platform Rotation		180°

Specifications subject to change

S

SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E

STANDARD EQUIPMENT

- 60 ft Platform Height
- 66 ft Working Height
- 36 × 96 in Platform Size
- 12 in Ground Clearance
- Proportional Hydraulic Controls
- Platform Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm
- 3/8" or 1/2" Airline to Platform

O

OPTIONAL

- Soft Touch System
- Fall Arrest System
- FMR System Fault Monitoring and Recording

MADE IN THE
USA 



Manufacturer of Custom
Aerial Lifts

manliftusa.com

sales@manliftusa.com