



S

SAFETY

- Explosion Proof
- Factory Mutual Approved
- Class 1, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

E

STANDARD EQUIPMENT

- 20 ft Platform Height
- 26 ft Working Height
- 28 x 84 in Platform Size
- 3.5 in Ground Clearance
- 900 lb Platform Capacity
- 300 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm
- Enhanced Padded Aircraft Rails
- 6 ft Powered Extendable Deck
- EX Rated LED Task Lighting

O

OPTIONAL

- Padded Aircraft Rails
- 3/8" Airline to Platform
- Drive / Lift-Lower Disable w/ Deck Extended
- Additional Battery Set w/ Removable Tray
- Scissor Stack Bellow

MSRP: \$172,471

2032EX-ALC EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS

| | | |
|---------------------------|----------------------|-------------|
| Working Height | 26 ft | 7.9 m |
| Raised Platform Height | 20 ft | 6.1 m |
| Lowered Platform Height | 38 in | 0.97 m |
| Platform Size (inside) | 28 x 84 in | 0.7 x 2.1 m |
| Platform Capacity | 900 lbs | 408 kg |
| Overall Width | 32 in | 0.8 m |
| Overall Length | 108 in | 2.75 m |
| Stowed Height | 77.5 in | 2.0 m |
| Deck Extension | 3 ft | 0.91 m |
| Ground Clearance (Stowed) | 3.5 in | 8.9 cm |
| Ground Clearance (Raised) | 0.75 in | 1.9 cm |
| Wheelbase | 69 in | 1.8 m |
| Inside Turning Radius | 50 in | |
| Outside Turning Radius | 108 in | 2.7 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | 0.7 mph | 1.1 km/h |
| Gross Weight | 5,700 lbs | 2,585 kg |
| Batteries | 4 x 6V 250 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |

Specifications subject to change

MADE IN THE
USA



Manufacturer of Custom
Aerial Lifts

manliftusa.com
sales@manliftusa.com